

Product: Surface BREVIS-D LED downlight



LED

**Description:**

The Brevis D (Diffuser) is a Ø195mm large area downlight which can be surface (Standard) or suspended mounted. The heatsink is built into the body of the product which enables the downlight to run at cool temperatures without the common need for vents in the vertical walls. The downlight also has an IP44 rating when surface mounted.

Physical attributes:

| | |
|-------------------|--------------------|
| Width: | 195mm diameter |
| Cutout: | surface mounted |
| Height: | 190mm |
| Ceiling type: | any |
| Mounting type: | Surface |
| Colour finish: | white |
| Dimming protocol: | DALI, mains, 1-10v |

**Lighting attributes:**


| | |
|----------------------|----------------------|
| LED manufacturer: | Bridgelux |
| Driver manufacturer: | Philips |
| Optics: | Frosted opal |
| Lumen output: | 1360, or 1800 lumens |
| Power consumption: | 15w or 20w |
| Colour temperature: | 3000K, 4000K |
| Colour consistency: | <3 Std MacAdam |
| Colour rendering: | Ra>80 |
| Rated LED lifetime: | 50,000 hours |
| Emergency pack type: | None |
| Warranty: | 5 years |
| Beam Angle options: | 60 or 90 degrees |



195



130

Efficiency in luminaire lumens per circuit watt: **91**