Product: PRO LINE suspended linear lighting up and down light with nano optics



LEC



## **Description:**

A high quality linear profile with up and down light and a 70 /30 split. Optics are nao prsim optics giving an UGR rating of less than 19. Profile can be finished in any RAL colour your project requires. Standard lengths from 565mm to 2245mm with longer lengths on request. Shortest profile with emergency gear is 900mm long. Suitable for commercial, residential or school applications. The nano-coating optics to improve lumen output, but also support continuous installation. The diffuser could be supplied independently as a continuous 30-metre PC roll for easy installation of a seamless continuous linear lighting line.

## **Physical attributes:**

Width: 50mm

Length: 565mm to 2245mm

Height: 70mm

Mounting type: Surface or suspended

Colour finish: White or Black
Dimming protocol: DALI or switching

## **Lighting attributes:**

LED manufacturer: Philips
Driver manufacturer: Philips

Optics: Nano optics UGR<19
Lumen output: 3100 to 11300lm
Power consumption: 30w to 122w
Colour temperature: 3000K or 4000K

Ra>80

Colour consistancy: <3 Std MacAdam

Rated LED liftime: 50,000 hours


Warranty: 5 years

65

Colour rendering:




An example of lighting shapes that can be achieved with the PRO LINE





info@silent.design



www.silent.design